
**Glass in building — General technical
requirements of building integrated
photovoltaic modules recycling**

用户名称： 中国水发兴业能源集团有限公司

订单号： 0100211203096095

购买日期： 2021-12-03

销售机构： 中国标准出版社

联系电话： 400-168-0010

网址： www.spc.org.cn



Reference number
ISO/TS 21480:2021(E)

© ISO 2021



扫描二维码查询标准授权信息

用户名称：中国水发兴业能源集团有限公司
订单号：0100211203096095
购买日期：2021-12-03
销售机构：中国标准出版社
联系电话：400-168-0010
网址：www.spc.org.cn

版权声明

国家市场监督管理总局、国家标准化委员会负责ISO、IEC国际标准在中国境内推广发行工作的监督和管理，负责ISO、IEC国际标准在中国境内的版权管理与保护工作。国家标准技术审评中心具体承担ISO、IEC国际标准在中国境内推广发行工作，承担ISO、IEC国际标准在中国境内的版权管理与保护工作。

中国标准出版社 为中国境内国际标准授权销售网站。

正版授权销售网站及销售点名单，可在国家标准信息服务网 (<https://www.sacinfo.cn/antifake>) 查询。

未经授权，严禁对ISO、IEC标准出版物及相关技术文件进行复制、销售、传播和翻译出版，严禁将国际标准的任何部分通过电子信息网络或制作成标准数据库用于传播。

国家标准技术审评中心 电话：400 650 6190 网址：www.sacinfo.cn

ISO/TS 21480:2021(E)

中国水发兴业能源集团有限公司专用

销售机构：中国标准出版社 网址：www.spc.org.cn 防伪查询：UPeg-r]S3-XawC-W7ZG-8fTw



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Fundamental principles.....	3
5 Classification.....	3
5.1 It can be classified according to the type of cell:.....	3
5.2 It can be classified according to the structure of encapsulation:.....	3
5.3 It can be classified according to abandoned condition:.....	4
6 Dismantlement.....	4
7 Collection, transportation and storage.....	6
7.1 General provisions.....	6
7.2 Collection.....	6
7.3 Transportation.....	6
7.4 Storage.....	7
8 Disassembly.....	7
8.1 General provisions.....	7
8.2 Termination.....	7
8.3 Frame.....	7
8.4 PV laminate.....	8
9 Treatment.....	8
9.1 General provisions.....	8
9.2 Glass.....	8
9.3 Interlayer.....	8
9.4 Solar cell.....	9
9.5 Welding strip.....	9
9.6 Plastic back sheet.....	10
10 Recovery.....	10
10.1 Semiconductor materials recovery.....	10
10.2 Metal materials recovery.....	11
10.3 Glass recovery.....	11
10.4 Polymer materials recovery.....	11
11 Management.....	12
Annex A (informative) Data collected for the information statistic system.....	13
Annex B (informative) Matters needing attention for recycling.....	14
Annex C (informative) Common requirements for work at height.....	15
Annex D (informative) Examples of requirements applicable to pollutants' emissions.....	16
Bibliography.....	17

防伪查询: UPeg-rfS3-XawC-WZG-8fTw

网址: www.spc.org.cn

销售机构: 中国标准出版社

ISO/TS 21480:2021(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 160, *Glass in building*, Subcommittee SC 1, *Product considerations*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Glass in building — General technical requirements of building integrated photovoltaic modules recycling

1 Scope

This document specifies requirements for the recycling of building integrated photovoltaic (BIPV) modules. It is suitable for crystalline silicon PV modules and thin film modules.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 472, *Plastics — Vocabulary*

ISO 11469, *Plastics — Generic identification and marking of plastics products*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

3.1 waste photovoltaic module waste PV module

photovoltaic module that the holder discards, or intends to discard, or is required to be discarded

3.2 laminated solar photovoltaic glass laminated solar PV glass

double glass photovoltaic module

double glass PV module

laminated glass that integrates the function of photovoltaic power generation

Note 1 to entry: This term covers both laminated glass (see ISO 12543-3) and laminated safety glass (see ISO 12543-2).

[SOURCE: ISO/TS 18178:2018, 3.1, modified — Photovoltaic has been changed to PV.]

3.3 hazardous material

item, element or substance with a potential for harm in terms of human injury or ill health (both short and long term), damage to property, damage to the environment, or a combination of these

[SOURCE: ISO 30000:2009, 3.5]

ISO/TS 21480:2021(E)

3.4 collection

logistical process of moving waste photovoltaic module from its source to a place where it can be recovered

[SOURCE: ISO 472:2013, 2.1682, modified — Domain of application has been deleted, and "plastics waste" has been changed to "waste photovoltaic module".]

3.5 storage

temporary storing activity of waste photovoltaic modules at a special place which meets the requirements for the purpose of *collection* (3.4), transportation, *treatment* (3.10) and *disposal* (3.11)

3.6 disassembly

set of activities of demounting and disintegrating waste photovoltaic modules by a manual or mechanical way for the convenience of *treatment* (3.10)

3.7 re-use

use of a product more than once in its original form

[SOURCE: ISO 472:2013, 2.1708, modified — Note to entry has been deleted.]

3.8 recycling

processing of waste materials for the original purpose or for other purposes, excluding energy recovery

[SOURCE: ISO 472:2013, 2.1706]

3.9 recovery

processing waste material for the original purpose or for other purposes, including energy recovery

[SOURCE: ISO 472:2013, 2.1704]

3.10 treatment

set of activities of decontamination, *disassembly* (3.6), comminution and *recycling* (3.8) of waste photovoltaic modules

3.11 disposal

set of activities for diminishment or elimination of the danger of waste photovoltaic modules

Note 1 to entry: This can be by means of changing physical, chemical and biological characteristics.

Note 2 to entry: The activities of final placement for waste photovoltaic modules in a place or facility that meets the requirements for environmental protection.

3.12 termination

component that is used to extract the direct current from photovoltaic module

3.13 photovoltaic laminate PV laminate

portion of a photovoltaic module consisting of substrate, encapsulant, complete photovoltaic cell circuit, and superstrate

Note 1 to entry: A photovoltaic module includes a laminate and a junction box. A frame and other accessories can also be added.

[SOURCE: IEC/TS 61836:2016, 3.1.50, modified — The preferred term has been changed to photovoltaic laminate.]

3.14 photovoltaic modules that lose safety performance

PV modules that lose safety performance

photovoltaic modules that have structural, electrical and other types of the safety risk

3.15

recovery rate

ratio of the weight of the recovery materials or components to the whole weight of the waste photovoltaic modules

4 Fundamental principles

4.1 The fundamental principles are the maximizing of resource utilization and the minimizing of environmental pollution.

4.2 The treatment shall be conducted according to the following order: re-use, recycling and energy recovery. The re-use and energy recovery should meet the requirements of related standards or specifications.

4.3 Treatment and disposal shall adopt the current optimal feasible technology. All necessary measures shall be employed in order to ensure that the effect of recycling process on personnel and the environment are in accordance with relevant standards during treatment and disposal.

4.4 The participants, including dismantlement, transportation and recycling organizations, shall establish appropriate information statistic systems for the collection, treatment and disposal of waste PV modules. The relevant data/information (see [Table A.1](#)) shall be saved and be available to competent departments or organizations.

4.5 Waste PV modules should not be landfilled or burnt directly.

4.6 Recovery materials or components should be used in PV modules.

4.7 Matters needing attention for recycling should be given (see [Annex B](#)) in the documentation of PV module.

5 Classification

5.1 It can be classified according to the type of cell:

- a) Crystalline silicon PV module;
- b) Copper indium gallium selenide (CIGS) PV module;
- c) Cadmium telluride (CdTe) PV module;
- d) Silicon-based thin film PV module;
- e) Other types of PV module.

5.2 It can be classified according to the structure of encapsulation:

- a) Single glass PV module;

ISO/TS 21480:2021(E)

- b) Laminated solar PV glass;
- c) Multi-layer glass PV module.

5.3 It can be classified according to abandoned condition:

- a) PV module that lose safety performance;
- b) PV module with damaged appearances, but the power generation performance works properly;
- c) PV module where the power generation performance shows obvious attenuation, but the appearances are not damaged;
- d) PV module with undamaged appearances and proper power generation performance, which the holder discards, or intends to discard for other causes.

NOTE Such PV modules can be reused without recycling.

6 Dismantlement

6.1 Dismantlement of waste PV modules shall avoid excessive emissions of pollutants, such as screw, rubber and metal components.

6.2 According to the methods of ISO 15928, the safety level of building after dismantlement of waste PV module should not be lower than that of building before dismantlement.

6.3 The electrical safety of the whole dismantlement should conform with the requirements of IEC 60364-7-704, IEC 60364-5-54 and IEC 60364-5-55.

6.4 The requirements related to the dismantlement of waste PV module can be found in national or local building safety codes.

6.5 Structure safety of buildings and safety of users shall be ensured during dismantlement process.

6.6 The system shall be electrically isolated before dismantlement, and it shall not be powered on until the whole system is repaired after being partly dismantled.

6.7 Safety nets should be installed in the working area to avoid tools and materials falling. Workers should be equipped with the safety devices such as safety helmets, safety ropes, safety shoes and safety clothes.

6.8 The integrity of PV modules should be ensured during the dismantlement process.

6.9 In order to avoid electric shock accidents, after the waste PV module is separated from the inverter, the cables of the module and inverter shall be insulated with insulating materials.

6.10 For cracked module, in order to prevent electric shock, the surface of the cracked waste PV module should be insulated in advance, if it is necessary to dismantle in rain and snow weather. Condition a) and b) should not be met at the same time:

- a) sunlight irradiates directly on module illumination side;
- b) human gets in contacts with the internal electrode of module directly or through conductive fluid.

6.11 For cracked module, before dismantlement, safety measures should be set to prevent the broken parts from falling.

6.12 The inner side of the building where waste PV module is disassembled shall be properly secured.

6.13 According to the disassembly height of the waste PV module, the appropriate size of the no walking area on the ground shall be set referring to [Table 1](#).

Table 1 — Determination of the size of the no walking area

Dismantlement height, h m	No walking area radius m
$2 \leq h \leq 5$	3
$5 < h \leq 15$	4
$15 < h \leq 30$	5
$h > 30$	6

6.14 During the entire dismantlement process, safety measures for waste PV module should be taken to avoid accidents such as module falling, severely swinging, and bursting, caused by operation, wind and rain, etc.

6.15 For waste PV module on the side of the building, if conditions permit, dismantlement work should be operated from the interior of the building rather than from outside the building.

6.16 If traffic is too heavy, the operation time should select the daytime period when traffic is not heavy. If the above condition cannot be met, the road can be temporarily closed, or the radius of the no walking area can be expanded.

6.17 In the case of wind speed greater than 10 m/s or other bad weather such as rain, thunder, snow and fog, the waste PV module dismantlement work should not be operated, unless authorized by national or local regulations.

6.18 Before dismantlement, workers shall clean the work area, and remove water, snow, oil, dust and other slippery materials from the surface of waste PV module components.

6.19 Before dismantlement, a safety plan shall be set according to building conditions. The workers shall track the safety of both the tool and the dismantling worker in real time during dismantlement process, avoiding accidents such as tool falling, rope breaking, unstable fixed point. The communication between the workers shall be clear.

6.20 Safety and construction equipment shall be fully prepared before waste PV module dismantlement work.

6.21 If the building of disassembled waste PV modules is in use, it should install new BIPV modules or materials with building function to repair the building immediately.

6.22 The dismantled modules should be recorded into the information statistics system to form a complete information system with the transportation and recycling parts.

6.23 The dismantlement of photovoltaic insulating glass units with PV power generation should avoid glass breakage caused by operation.

6.24 The accessories of BIPV modules should be removed during the dismantlement processing. If the accessories cannot be removed on the spot, these modules should be collected separately, and the accessories should be removed before recycling processing.

防伪查询：UPeg-rJS3-XawC-W7ZG-8fTtw
www.spc.org.cn
网址：
销售机构：中国标准出版社

ISO/TS 21480:2021(E)

6.25 The requirements related to dismantlement work can be found in national or local regulations for work at height.

NOTE Refer to [Annex C](#) for common requirements for work at height.

7 Collection, transportation and storage

7.1 General provisions

7.1.1 In the process of collection, transportation and storage, the harm caused by electric leakage of solar cell shall be prevented.

7.1.2 For PV modules that lose safety performance, these shall be classified prior to collection, transportation and storage. This shall be conducted in a manner that ensures personal injury is avoided.

7.1.3 For PV modules having risk of heavy metals leakage, these shall be classified prior to collection, transportation and storage. This shall be conducted in a manner that ensures environmental pollution is avoided.

7.1.4 PV modules shall avoid secondary pollution influencing the recycling, such as oil pollution and saline-alkali corrosion.

7.1.5 Sort waste PV modules according to the size and shape of waste PV modules before transportation and storage.

7.2 Collection

7.2.1 Waste PV modules shall be prohibited from being mixed with domestic garbage or industrial solid waste.

7.2.2 Collected waste PV modules shall be stored according to the requirements of [7.4](#).

7.2.3 Collector shall deliver collected waste PV modules to qualified organizations for disassembly and treatment.

7.2.4 Protection measures shall be set up to avoid harming of modules and broken components falling in the process of collection, such as broken glass, interlayer, termination, cable and solar cell, which can cause injury or pollute the environment.

7.3 Transportation

7.3.1 The waste PV module should be recorded in the statistical information management system before transportation.

7.3.2 In the process of transportation, unauthorized disassembly and treatment to waste PV modules shall not be conducted in any form.

7.3.3 Protective measures shall be set up to avoid harming of modules and broken components falling in the process of transportation, such as broken glass, interlayer, termination, cable and solar cell, which can cause injury or pollute the environment.

7.3.4 Secondary pollution to waste PV modules shall be prevented in the process of transportation, especially oil pollution and saline-alkali corrosion. Transportation organization should connect with a

recycling organization to ensure whether the recycling process requires avoiding secondary damage to PV modules or other requirements.

7.4 Storage

7.4.1 Requirements for the storage site of waste PV modules can be found in the relevant regulations, i.e. national and local laws and regulations.

7.4.2 All kinds of waste PV modules shall be classified prior to storage and all module types (see 5.1) shall be appropriately marked at prominent positions.

7.4.3 It shall be guaranteed that pollutants, such as broken glass, solar cell, termination and cable, cannot drop down during storage, avoiding pollution to environment.

7.4.4 Secondary pollution, especially oil pollution and saline-alkali corrosion, should be prevented during storage. Storage organization should connect with a recycling organization to confirm whether the recycling process requires avoiding secondary damage to PV modules or other requirements.

8 Disassembly

8.1 General provisions

8.1.1 It shall be strictly prohibited to discard any part of waste PV modules, which are taken out in advance.

8.1.2 Materials and all the taken-out parts shall be stored in appropriate classified containers and be marked clearly. Hazardous material should be classified correctly and stored carefully avoiding dangers to personnel and pollutants to environment.

8.2 Termination

8.2.1 The gas containing dust, which is produced in the process of sorting and crushing, shall be dealt with by the waste gas processing system. After treatment, waste gas should conform with the relevant requirements shown in [Table D.1](#).

8.2.2 After the treatment of scrap wire and cable, all metals, plastic and rubber shall be recycled.

8.2.3 Termination waste should not be landfilled directly.

8.2.4 Waste water, produced in the process of waste termination cleaning, should be dealt with by the waste water treatment system, and should be recycled. After treatment, waste water should conform with the relevant requirements shown in [Table D.1](#).

8.3 Frame

8.3.1 The frame should be mechanically disassembled before other recycling processing.

8.3.2 Mechanical disassembly shall be performed in a manner that prevents disassembled metal components from hurting workers.

8.3.3 After disassembly, the metal components that can be directly recycled should be subjected to cleaning, polishing and edge grinding.

ISO/TS 21480:2021(E)

8.3.4 After disassembly, the metal components that cannot be directly recycled shall be subjected to other environmentally friendly processes, e. g. melting, extraction, etc., and the processes shall guarantee no leakage.

8.4 PV laminate

8.4.1 Hot-melt methods or chemical techniques can be used to decompose interlayer while recycling PV laminate. Then the glass or organic back sheet should be peeled from the PV laminate. The integrity of the PV laminate should be ensured as far as possible.

8.4.2 A mechanical or chemical method can be used to separate the welding strip and the solar cell.

8.4.3 A mechanical method can be used to break the left PV laminate parts into small pieces. A dust collection system should be used during this process.

8.4.4 Multi-layer glass PV modules should be disassembled to glasses and laminated solar PV glass, then following the recycling processing of laminated solar PV glass.

8.4.5 The disassembly of photovoltaic insulating glass units should take the desiccant collection into consideration, avoiding desiccant pollution to environment. If the heat method is adopted, the disassembly should also consider poisonous gases during the high temperature processing during which the following should not be adopted: too high temperature or poisonous gases treatment.

9 Treatment

9.1 General provisions

9.1.1 When a hot-melt method and other heating methods are used to treat waste PV modules or parts of PV modules, waste gas treatment facilities shall be employed and the emissions of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.1.2 When an incinerating method is used to treat waste PV modules or parts of them, the emissions of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.1.3 Waste water and liquid produced in the process of treatment shall be disposed, and the emission of pollutant should meet the relevant requirements shown in [Table D.1](#).

9.2 Glass

9.2.1 In the treatment process of thermal decomposition of glass, waste gas treatment system shall be employed to control the amount of impurity in waste gas. Any contaminants/pollutants produced should meet the relevant requirements shown in [Table D.1](#).

9.2.2 When incinerating or hot-melt method is used to process glass, waste gas treatment facilities shall be employed. The emissions of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.3 Interlayer

9.3.1 After peeling the interlayer, it shall not be sent to land fill directly.

9.3.2 When an incinerating or hot-melt method is used to process interlayer, waste gas treatment facilities shall be equipped. And the emissions of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.3.3 After the hot melting of interlayer, the residue shall be recycled according to its physical and chemical characteristics.

9.4 Solar cell

9.4.1 In the recycling treatment of crystalline Si or Si thin film solar cells, there should be no polymer materials residue, and silicon solar cell may be recycled as silicon powder or silicon wafer according to the damaged condition.

9.4.2 Silver, aluminum and other metal impurities can be removed from silicon powder by a chemical method, and the emission of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.4.3 Entirely recycling uses chemical method for cleaning, corroding the surface coating, and finally for the polishing treatment. The discharge of waste water of the recycling process should meet the relevant requirements shown in [Table D.1](#).

9.4.4 When an acid dissolution method is used to process solar cells, it shall be guaranteed that there is no leakage. Acid gas produced in reaction time shall be treated, and the emission of pollutants should meet the relevant requirements shown in [Table D.1](#). After the treatment of waste liquid, the emission of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.4.5 When the heat treatment method is used, waste gas treatment facilities shall be employed. The emissions of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.4.6 When precious metal materials are extracted from solar cells, it shall be guaranteed that there is no leakage. Acid gas and waste liquid produced in reaction time shall be treated, and the emission of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.4.7 Protection measures should be set up to avoid polluting the environment or harming human health in the process of treatment.

9.5 Welding strip

9.5.1 The recycling of welding strip can generally use heat method or chemical etching to remove the surface tin and lead, in order to obtain high-purity copper. For aluminum welding strip used in thin film modules, it can be directly recycled in order to obtain high-purity aluminum.

9.5.2 The recovery purity of copper should attain 99,5 %. For aluminum welding strip used in thin film modules, the recovery purity of aluminum should attain 99,5 %. For the welding strip with known weights of copper and aluminum, the recycling technologies should attain 90 % recovery rate for each of these metals.

9.5.3 When lead of the welding strip is removed by chemical etching method, the treatment of the solution should meet the relevant requirements shown in [Table D.1](#).

9.5.4 When tin of the welding strip is removed by chemical etching method, the treatment of the solution should meet the relevant requirements shown in [Table D.1](#).

ISO/TS 21480:2021(E)

9.5.5 When extracting precious metal materials by chemical solution method, it shall be guaranteed that there is no leakage. Acid gas produced in reaction time shall be treated, and the emission of pollutants should meet the relevant requirements shown in [Table D.1](#). After the treatment of waste liquid, the emission of pollutants should meet the relevant requirements shown in [Table D.1](#).

9.5.6 After treatment, the discharge of waste gas and liquid, which are produced in the process of waste copper recycling, should meet the relevant requirements shown in [Table D.1](#). Protection measures should be set up to avoid sharp metal strip causing injury, metal component falling and polluting the environment.

9.5.7 In the process of waste metal collection, transportation, storage and disassembly, suitable measures should be taken to avoid causing secondary pollution to the environment.

9.5.8 The copper after treatment can be divided into different categories according to the physical form and the name. Each kind of copper is divided into different groups according to different types of production, and each group is distinguished between different levels according to the name of the scrap copper. If copper recycled shows different quality in terms of purity or alloy component, it should be classified in accordance with EN 12861.

9.5.9 Tin and tin alloys should be classified by scrap purchasing enterprises in terms of different chemical component, physical form and existing way.

9.6 Plastic back sheet

9.6.1 If peeling back sheet by heating method, the heating temperature of the back sheet containing fluoride should not be too high according to the materials of back sheet, in order to prevent the production of poisonous gas like hydrogen fluoride.

9.6.2 Peeled back sheet materials shall not be discarded arbitrarily. Requirements for their recycling can be found in national or local treatment regulations for halogen-containing plastic products. The treatment of materials that cannot be recycled shall be in accordance with the treatment requirements of general industrial solid waste.

9.6.3 When an incinerating method is used to treat back sheet (containing fluoride or not), waste gas treatment facilities shall be employed, and the emissions of pollutants should meet the relevant requirements shown in [Table D.1](#). When landfill is used for treatment, the emission of pollutants should meet the relevant requirements shown in [Table D.1](#).

10 Recovery

10.1 Semiconductor materials recovery

10.1.1 The recovery of silicon materials generally uses a chemical method to remove the positive and negative electrodes, antireflection film, p-n junction and so on, in order to obtain recyclable high-purity silicon materials.

10.1.2 For modules with a known weight of silicon, the recycling technologies should attain 90 % recovery rate for silicon.

10.1.3 Silicon powder, which is purified twice according to the relevant requirements, can be suitable for semiconductor industry, and it may be treated by landfill when no heavy metals are contained.

10.1.4 Undamaged recovery silicon wafer may be used again in the photovoltaic industry.

10.2 Metal materials recovery

10.2.1 The purification of precious metals in solar cells may generally use the method of reduction after solvent corrosion for regeneration.

10.2.2 The purity of silver should attain 99,5 %. For modules with a known weight of silver, the recycling technologies should attain 90 % recovery rate for silver.

10.2.3 The purity of copper, indium, gallium and selenium should attain 90 %. For CIGS thin film modules with known weights of copper, indium, gallium and selenium, the recycling technologies should attain 90 % recovery rate for each of these metals.

10.2.4 For CdTe thin film module, the purity of cadmium and tellurium should attain 98 %. For CdTe thin film modules with known weights of cadmium and tellurium, the recycling technologies should attain 95 % recovery rate for each of these metals.

10.2.5 After treatment, the discharge of waste gas and liquid, which are produced in the process of scrap metal recovery, should conform with the relevant requirements shown in [Table D.1](#).

10.2.6 Requirements for recovery metal products can be found in national or local regulations for metal products.

10.2.7 Requirements for the discharge of waste water can be found in relevant local standards.

10.3 Glass recovery

10.3.1 After treatment, light transmittance and strength of undamaged glass should conform with the requirement of re-use purpose. If re-used in the production of PV modules, it should follow the usual requirements of glass for PV modules.

10.3.2 Requirements for recycled and undamaged glass can be found in national or local regulations for glass products.

10.4 Polymer materials recovery

10.4.1 In the recovery treatment of waste PV modules, the waste gas and liquid produced in the treatment process of polymer materials should be collected and be treated in a harmless way. After that, waste plastics shall be classified for re-use.

10.4.2 Waste plastic containing flame retardants can only be applied to plastic products raw materials containing flame retardants.

10.4.3 Requirements for recovery plastic products or materials can be found in national or local regulations for plastic products. A recovery logo shall be marked on the surface and conform with the relevant requirements of ISO 472 and ISO 11469.

10.4.4 In the production process of recovery plastic products or materials, chloro-fluoro-carbons shall not be used as foaming agent. Poisonous and harmful chemical additives shall not be utilized to improve recycle raw material plastic characteristic when the final product could come in contact with human being.

ISO/TS 21480:2021(E)

11 Management

11.1 Recycling organizations shall establish a system of record for the whole recycling process.

11.2 Recycling organizations shall keep records of treatment related to waste PV modules, pollutant monitoring and other relevant processes for at least three years. They can also be required to be inspected by local authorities.

11.3 Recycling organizations shall have the corresponding environmental protection facilities, including waste water treatment, waste gas treatment, dust treatment and noise reduction devices, and the discharges of pollutants shall meet the relevant national standards. The pollutant concentration in the discharge of waste water and waste gas should be monitored regularly. The noise at the boundary of the industrial premises should be monitored regularly. Requirements for its level can be found in national and local laws and regulations.

11.4 Recycling organizations shall establish emergency handling procedures, and have a complete protective equipment system and measures. Requirements for the operation can be found in national and local laws and regulations.

11.5 New workers shall conduct pre-service training or operation under the guidance of the technician.

11.6 The operation and management of the recycling organization should meet the requirements of ISO 14001, ensuring that the discharge of the three wastes meets the national or local standards, the recycling operation information is fully monitored, and the potential dangers of personal safety and environmental pollution are avoided.

Annex A (informative)

Data collected for the information statistic system

Table A.1 — Data collected by different participants for the information statistic system

	Dismantlement organization	Transportation organization	Recycling organization
1	date of dismantlement	date of transportation	date of recycling
2	building function of waste PV module	location of waste PV module collection	recycling material category
3	BIPV project location	destination	weight of recycling materials
4	module type	module type	module type
5			module size
6			module weight
7			greenhouse gases of recycling process
8			date of manufacture
9			BIPV manufacturer
10			BIPV project location
11			reason of discard
12			date of dismantlement
13			date of transportation

NOTE 1 The data in the table or other data are optional for the information statistic system.

NOTE 2 Building function of waste PV modules can be curtain wall, sunroof, handrail, carport and roof.

NOTE 3 Recycling materials categories can include Si, Ag, Cu, In, Ga, Se, Al, Te, Cd, glass, etc.

NOTE 4 Greenhouse gases emission management of organization and project level should conform with ISO 14064.

NOTE 5 For module type, see 5.1 and 5.2 for reference.

销售机构：中国标准出版社 网址：www.spc.org.cn 防伪查询：UPeg-rjS3-XawC-W7ZG-8fTw

Annex B (informative)

Matters needing attention for recycling

Information to be given in the documentation:

1. People should meet the requirements of this document during recycling process.
2. Principles that people should conform with during recycling process.
3. The weight of material contained in the PV module can include:
 - a) frame;
 - b) glass;
 - c) welding strip;
 - d) termination;
 - e) PV cell;
 - f) interlayer;
 - g) transparent conduction oxide layer (TCO);
 - h) back sheet;
 - i) substrate;
 - j) encapsulant;
 - k) other material.
4. The hazardous material contained in the PV module and its position in the PV module can include:
 - a) Cd, can be contained in CdTe PV cell;
 - b) Pb, can be contained in welding strip;
 - c) fluorine, can be contained in back sheet.

Annex C (informative)

Common requirements for work at height

1. Workers shall take training of work at height, obtaining related certification.
2. The training of work at height shall reach professional level.
3. Workers shall take a physical examination at least once a year, ensuring that they are physically fit to work at height.
4. A sign of no walking area shall be displayed at the ground of working site.
5. Communication equipment shall be used during process of the work.
6. Necessary precaution shall be taken when working close to high-voltage power line, for example cutting off the power before any work can start.
7. Simultaneous work at different level of the same section shall be avoided. If necessary, a protective shield or other separation measure shall be set between the two working positions.
8. Work at height under severe weather shall be forbidden.
9. Equipment shall be check carefully before the start of work.
10. The duties of workers, designers and officers shall be clearly defined.
11. All precaution shall be taken to minimize risks at work.
12. A work flow process shall be set up prior to work.

Annex D (informative)

Examples of requirements applicable to pollutants' emissions

The processing of pollutants' emissions should conform with the requirements in Table D.1.

Table D.1 — Examples of requirements applicable to pollutants' emissions

Pollutant	Requirement
Atmospheric pollutants	Conform with the relevant requirements of ISO 14001, 14004 and 14031.
Waste liquid/gas	
Dust	
Waste liquid containing lead	Conform with the relevant requirements NOTE National and local laws and regulations might exist.
Waste liquid containing tin	

中国水发兴业能源集团有限公司

Bibliography

- [1] ISO 14004, *Environmental management systems — General guidelines on implementation*
- [2] ISO 14031, *Environmental management — Environmental performance evaluation — Guidelines*
- [3] ISO 14001, *Environmental management systems — Requirements with guidance for use*
- [4] ISO 14064 (all parts), — *Greenhouse gases*
- [5] ISO 15270:2008, *Plastics — Guidelines for the recovery and recycling of plastics waste*
- [6] ISO 15928 (all parts), *Houses — Description of performance*
- [7] ISO/TS 18178:2018, *Glass in building — Laminated solar photovoltaic glass for use in buildings*
- [8] ISO 30000:2009, *Ships and marine technology — Ship recycling management systems — Specifications for management systems for safe and environmentally sound ship recycling facilities*
- [9] IEC 60364-5-54, *Low-voltage electrical installations - Part 5-54: Selection and erection of electrical equipment - Earthing arrangements and protective conductors*
- [10] IEC 60364-5-55, *Electrical installations of buildings -Part 5-55: Selection and erection of electrical equipment - Other equipment*
- [11] IEC 60364-7-704, *Low-voltage electrical installations - Part 7-704: Requirements for special installations or locations - Construction and demolition site installations*
- [12] IEC/TS 61836:2016, *Solar photovoltaic energy systems - Terms, definitions and symbols*
- [13] EN 12861, *Copper and copper alloys- Scrap*
- [14] EN 50583, *Photovoltaics in buildings*

ISO/TS 21480:2021(E)

中国水发兴业能源集团有限公司专用

销售机构：中国标准出版社 网址：www.spc.org.cn 防伪查询：UPag-fjS3-XawC-W7ZG-8fTtw

ICS 81.040.20

Price based on 17 pages

© ISO 2021 - All rights reserved