




利 帅 影 视



**LISHUAI FILM &
TELEVISION EQUIPMENT**



About us


ENTERPRISE INTRODUCTION

Established in 2003, Yuyao Lishuai Film & Television Equipment Co., Ltd is a high-tech enterprise integrating R&D, production and sales of LED photo and video lighting equipments and accessories, and has passed ISO9001 certification.

Since 2006, the company has been mainly committed to the application of various LED lights in the film and photography industries. Up to now, the LS brand and products are specially preferred by film crews, program groups, TV stations, advertisers, lighting engineers, photographers and cameramen.

During the company's development, we adhered to the principle of "taking honesty as foundation, self-surpassing and creative". By present the company has obtained 2 Invention patents, 36 Utility Model patents and Design patents and has been recognized as a "National High-tech Enterprise" for three years since 2014. Every year the company develops sino-foreign cooperation projects and by now has cooperated with several well-known enterprises at home and abroad and has achieved good results. By now the company's current products have passed CE certification.

By steady efforts, our products have been sold far to Europe, America, Middle East, Southeast Asia and Hong Kong, Macao and Taiwan regions, many provinces and cities in china. Customer's trust is always our company's pursue and company's development is inseparable from the support of customers. We sincerely welcome you to join us for future development.





FOCUS 1000X_{PRO} Specifications

- ✓ **500W+500W Bi-color**
- ✓ **High CRI 95**
- ✓ **Taiwan imported LED**
- ✓ **MW Power adapter**
MEAN WELL
- ✓ **Outdoor rainproof**



FOCUS 1000X_{PRO}

500Wx2
High power



11
special effects



FOCUS 1000X_{PRO}

LED	1000W COB
Beam angle	120°
CRI	95
Color temperature	2700K-6500K
TLCI	95
Power	500W daylight+500W tungsten(600W max)
Working voltage	AC100-240V,DC36-48V
Cooling system	Heat pipe radiator , Temperature controlled fan
Dimension (light body)	10.4 x 12.1x16.8" (263x307x426mm)
Dimension (power control box)	12.8x 7.3 x8.3" (325x185x212mm)
Weight	Light body: 12.1 lb (5.49kg), Power control box: 18.3 lb (8.3kg)



✓ **300W+300W Bi-color** **FOCUS 600D/X**

✓ **High CRI 95 +**

✓ **Taiwan imported LED**

✓ **MW MEAN WELL** Power adapter



Control box with handle,
easy to carry



Remote control or APP control



LCD display



Bowens mount





FOCUS 600D/X Specifications

FOCUS 600D

LED	600W COB
Beam angle	120°
CRI	≥96
Color temperature	5600K±300K
TLCI	≥96
Power	600W
Working voltage	AC100-240V,DC36-48V
Cooling system	Heat pipe radiator, Temperature controlled fan
Dimension (light body)	10.4 x 12.1x16.8" (263x307x426mm)
Dimension (power control box)	12.8x 7.3 x8.3" (325x185x212mm)
Weight	Light body: 12.1 lb (5.49kg), Power control box: 11 lb (5kg)

[600D illuminance]

Distance	Light without reflector	Light with standard reflector
1m	21481 Lux	> 300000Lux
2m	5672 Lux	50545 Lux
5m	1124 Lux	6094 Lux
10m	317 Lux	1492 Lux



FOCUS 600X Bi-color

LED	600W COB
Beam angle	120°
CRI	≥95
Color temperature	2700K-6500K
TLCI	≥95
Power	300W daylight+300W tungsten(500W max)
Working voltage	AC100-240V,DC36-48V
Cooling system	Heat pipe radiator, Temperature controlled fan
Dimension (light body)	10.4 x 12.1x16.8" (263x307x426mm)
Dimension (power control box)	12.8x 7.3 x8.3" (325x185x212mm)
Weight	Light body: 12.1 lb (5.49kg), Power control box: 8.5 lb (3.85kg)

[600X illuminance without reflector]

Distance	Temperature		Color illuminance		
	2700K	3200K	4400K	5600K	6500K
1m	7162Lux	9103Lux	14005Lux	10729Lux	9077Lux
2m	1929Lux	2467Lux	3713Lux	2910Lux	2461Lux
5m	378Lux	485Lux	735Lux	568Lux	481Lux
10m	108Lux	137Lux	206Lux	162Lux	139Lux

[600X illuminance with standard reflector 15°]

Distance	Temperature		Color illuminance		
	2700K	3200K	4400K	5600K	6500K
1m	110100Lux	143500Lux	204300Lux	172000Lux	133400Lux
2m	15754Lux	21256Lux	31444Lux	25475Lux	21204Lux
5m	1985Lux	2577Lux	3915Lux	3096Lux	2685Lux
10m	486Lux	623Lux	952Lux	756Lux	651Lux



✓ **150W+150W Bi-color** FOCUS **300D/X**

✓ High CRI **95 +**

✓ Taiwan imported LED

✓ **MW** Power adapter
MEAN WELL



Remote control or APP control



Bowens mount



Support household AC power supply or power control box with V-lock battery



Stepless dimming



LISHUAI FILM &
TELEVISION EQUIPMENT



High brightness



95⁺

High CRI



Bowens mount



11 special effects



Taiwan imported LED



Remote control or
APP control

FOCUS 150D II
150W High power

80W+80W Bi-color

FOCUS 150X



Remote control or
APP control






200W High power
FOCUS 200D II





Specifications:

150D II 150X 200D II 300D II 300X

Model	 Focus 150D II	 Focus 150X	 Focus 200D II	 Focus 300D II	 Focus 300X
Color temperature	5600K±200K	2700K(±200K) ~6500K(±300K)	5600K±200K	5600K±200K	2700K(±200K) ~6500K(±300K)
CRI	96+	95+	96+	96+	95+
TLCI	96-98	95-98	96-98	96-98	95-98
AC power supply	AC100-240V	AC100-240V	AC100-240V	AC100-240V	AC100-240V
DC power supply	DC15-24V	DC15-24V	DC15-24V	DC24-34V	DC24-34V
Power	150W(Max)	120W(Max)	200W(Max)	300W(Max)	300W(Max)
Remoting mode	Remote control +APP	Remote control +APP	Remote control +APP	Remote control +APP	Remote control +APP
Remote control is optional	Yes	Yes	Yes	Yes	Yes
Dimming	0%-100%	0%-100%	0%-100%	0%-100%	0%-100%
Lighting effects	11	11	11	11	11
DMX	Support	Support	Support	Support	Support
Power control box	Integrated	Integrated	Integrated	Separate	Separate
Multi lamp interconnection	Support	Support	Support	Support	Support
Cooling system	Fan	Fan	Fan	Fan	Fan
Aluminum housing	Yes	Yes	Yes	Yes	Yes
Firmware update	/	/	/	Support	Support
Mount	Bowens mount	Bowens mount	Bowens mount	Bowens mount	Bowens mount
Dimension	230x130x265mm	230x130x265mm	230x130x265mm	229x207x313mm (light body) 160x133x290mm (power control box)	229x207x313mm (light body) 160x133x290mm (power control box)
Weight	2.7kg	2.7kg	2.7kg	3.41kg (light body) 3.8kg (power control box)	3.41kg (light body) 3.8kg (power control box)



FN1815



Product material	Nylon + glass fiber, optical glass
Dimension	φ180* (140-195) mm
Weight	1.09kg
Suitable for models	150D/X,200D,300D/X
Mount	Bowens mount
Accessories available	Honeycomb,barndoor,color filters
Angle	12°-40°

SN1980



Product material	Aluminum alloy shell, Nylon + glass fiber, optical glass
Dimension	φ195* (325-365) mm
Weight	2kg
Suitable for models	150D/X,200D,300D/X,600D/X,1000X
Mount	Bowens mount
Accessories available	Gobo discs,Gobo holder, Color filter holder,Spotlight iris
Angle	20°

Deep parabolic Softbox



Model	P70,P90,P120,P150
Product material	Selected high temperature resistant soft light fabric
Dimension	Diameter:70cm,90cm,120cm,150cm
Suitable for models	150D/X,200D,300D/X,600D/X,1000X
Mount	Bowens mount
Accessories included	White diffusion cloth
Accessories available	Cloth light guide grid

Lantern Softbox



Model	SBL65,SBL80,SBL100,SBL120
Product material	Selected high temperature resistant soft light fabric
Dimension	Diameter:65cm,80cm,100cm,120cm
Suitable for models	150D/X,200D,300D/X,600D/X,1000X
Mount	Bowens mount



LS-250T



Max height	2420mm
Min height	840mm
Folded height	735mm
Weight	1.75kg
Sections	4
Pipe dia	19mm, 22.4mm, 26mm, 29.5mm
Loading weight	3kg

LS-260F



Max height	2600mm
Min height	1100mm
Folded height	1100mm
Weight	3.8kg
Sections	3
Pipe dia	25mm, 30mm, 35mm
Loading weight	6kg

LS-270F



Max height	2700mm
Min height	1100mm
Folded height	1100mm
Weight	5.1kg
Sections	3
Pipe dia	25mm, 30mm, 35mm
Loading weight	10kg

CA119



Size	140x70x36mm
Weight	0.23kg
Loading weight	30kg
Pipe dia	20mm-35mm
Threaded hole	1/4" 3/8"

CA120



Size	140x70x43mm
Weight	0.23kg
Loading weight	30kg
Pipe dia	20mm-35mm
V mount	with 1pc

CA121



Size	145x147x43mm
Weight	0.45kg
Loading weight	30kg
Pipe dia	20mm-35mm
Threaded hole	1/4" 3/8"
V mount	with 2pcs



YUYAO LISHUAI FILM & TELEVISION EQUIPMENT CO.,LTD

Add: No.55 East Zhenxing Road, Yuyao City, Zhejiang Province, China

Tel: +86-574-62763333/62636368 Fax: +86-574-62636368

Email: ls@lishuai.com.cn

Http://www.lishuai-lighting.com www.led-studiolights.com