



Face Material

weight	thickness	material
20 ± 10%g/m² ISO 536	0.019 ± 10%mm ISO 534	Transparent Matte BOPP Film

Adhesive

The adhesive of this material is very strong, with waterproof effect, able to resist water flushing, can penetrate into the concave surface to stick firmly. Especially its function to full the softener which leak from the surface of the tyre, making it more difficult to fall off. It's suitable for premium tyre labelling, also particularly for cloth, leather and so on which are very difficult to stick on. For delivery, with durable property.

Peel adhesion

Initial adhesion 2N/25mm FTM 9 st.st	20 minutes Peel adhesion value on steel at 180° 2N/25mm FTM 1 st.st	20 minutes Peel adhesion value on steel at 90° 2N/25mm FTM 2 st.st
--	--	--

Temperature

Min. Appl. Temp. 10 °C	Service Temp. -10°C+60°C (after 24hrs)
---------------------------	---

Applications

Waterproof and oil-proof; can enhance the protection and increase the smoothness of the printed label; cold mounting, can be directly applied to the printed label without heating.

The above suggestion, application, and elaboration are not intended as the guarantee of Siga. All sales of Siga products shall be tested by customer in the final environment to confirm compliance with the requirements of the use of environment.

Shelf life

12 months, applicable only to the material delivered by Siga which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 23 ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.