



Face Material					
weight		thickness		Roughness	
70 ± 6g	ISO536	0.70mm ± 10%	ISO534	SO8791/4 ≤ 1.4 μm	
Brightness		Gloss		Opacity	
ISO 2470	75 ± 1.5 %	T480	80 ± 5 %	ISO 2471	98 ± 1.5 %

Applications

A top coated thermal paper. This product adopts smooth bright white paper with heat-sensitive coating, which has good wet friction resistance and certain water resistance, suitable for supermarket price labels and medium and low speed barcode printers.

The above suggestion, application, and elaboration are not intended as the guarantee of Siga. All sales of Siga products shall be tested by customer in the final environment to confirm compliance with the requirements of the use of environment.

Printing Methods

It can be applied to various printing methods such as flexographic printing, letterpress printing and screen printing, and has good expressiveness to ink. Due to the heat sensitivity of the product, the processing environment exceeding 50°C should be avoided. Excellent die-cutting characteristics on all customary machines.

Shelf life

12 months, applicable only to the material delivered by Siga which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 23 ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.