

Full Height Turnstile

Wide interior curved design dual-way all stainless turnstile 2.3M high.

SUS304 Stainless • Semi or Fully Automatic capabilities • IPX4 Protection • 5 Year Warranty • 10+ Years' Experience.

Introduction

The full height turnstile is assembled to provide a ridged steel framework shell. Ideal for outdoor installations as it provides high durability and tensile strength. All parts made with SUS304 1.5-3.0mm stainless steel material to provide rustproof and high quality durability.

The turnstile can be set to be always be push revolved in an emergency, thus, allow unhindered passage.



SSH-6081

Technical Specifications

General Specifications

Start-up Time	3s(semi-automatic),8s(full-automatic)
Time to open Gate	0.2 seconds
Direction	Single or bidirectional
Working environment	Indoor or outdoor
Ingress Protection	IP45
Pass speed	30~35 persons/minute
Operational life	>3 million
Working temperature	Indoor/outdoor (with a tent over) -10°C—50°C Relative humidity: ≤90%, no condensation
Communication Interface	RS485, TCP/IP.

Physical

Dimensions	2400mm x 1350mm x 2300mm
Housing Material	SUS304 1.5-2.0mm stainless steel optional to use SUS316L
Weight	400 kg / 882 lb
Input interface	Dry contact signal or +12V level signal or DC12V pulse signal with a width of more than 100ms. Driving current: > 10mA

Electrical

Working voltage	AC110/220 ±10% V/50 ±10% HZ (specify when ordering)
Electronic motor	Brushless motor 24V 40W with fully auto option
Power Consumption	6A

Extra

Options.	SUS 316, Powder coating finish, coloured style for LEDs or. User RFID reader fitting cradle.
----------	--

Standard Functionality

- » Alarm Function.
- » Passage width 650mm
- » High visible LED direction arrow plate.
- » Swipe card memory function.
- » External long-range management and control via computer.
- » Optional with Face detection biometric.
- » Five-year warranty.

CAD Dimensions

